



1778-VXL

3/4" VIBROTHERM DRIVE COMPOSITE IMPACT WRENCH

FEATURES

- Provides 1,450 ft-lb maximum torque and 1,700 ft-lb of loosening torque
- VIBROTHERM DRIVE® impact wrenches incorporate the new patented AIRCAT design impact wrench mechanism
- The new mechanism reduces vibration levels by 30%-40% and increases the life of the mechanism by 50%
- The latest patented AIRCAT muffler system provides the AIRCAT's unmatched low noise levels
- The patented grip design provides the customary AIRCAT operator comfort
- Investment in tooling, materials, and the triple injection molding processes enables AIRCAT® to produce cosmetic designs that are unmatched in the industry

SPECIFICATIONS

Loosening Torque (ft-lb) @90psi	1,700
Square Drive (in.)	3/4
Bolt Capacity (in.)	1
Free Speed (RPM)	5,400
Impacts Per Minute (IPM)	1,300
Weight (lbs.)	7.4
Length (in.)	7.4
Noise Level d(B)A	94
Vibration Level (m/sec2)	6.5
Rec. Hose Size (in.)	1/2
Air Inlet (in.) NPT/BSP	3/8

VIBROTHERM by AIRCAT DRIVE®



Styled for perfection and built to last!

AIRCAT

a Division of Florida Pneumatic Manufacturing Corporation
851 Jupiter Park Lane / Jupiter, Florida 33458

www.AIRCAT.com

(800) 356-3392